



LIONSHEAD

NO EXCUSES Guaranteed!

At Lionshead, we are so confident in the performance of our tires and wheels, we will replace **any ST radial tire** for **any reason** for the first twelve (12) months from date of retail sale.

This guarantee is part of our industry leading,

"1•2•5 Lifetime Program"



1 Year (First Year) "No Excuses Guarantee"

If the consumer has any issues with their tire in the first twelve (12) months (from date of purchase), Lionshead will replace that tire at no charge. Lionshead will also provide a flat labor rate to assist in the cost of mounting the new tire.



2 Year Complimentary Roadside Assistance

Owner can use this program to have a service technician come out and remove the damaged assembly and install the inflated spare at any time.



5 Year Warranty on Radial ST Tires

Five year protection from all manufacturer's defects.



Lifetime Structural Warranty on All Wheels

Lifetime protection from all manufacturer's defects on all wheels.

305 Stuary Avenue, Goshen, Indiana 46528
Phone: (574) 533-6169

President: Tim Miller
(260) 341-0210 • tmiller@lionsheadtireandwheel.com

National Sales Manager: Connor Kruggel
(719) 640-9801 • ckruggel@lionsheadtireandwheel.com

National Sales Manager: John Graham
(574) 971-1788 • jgraham@lionsheadtireandwheel.com





LIONSHEAD

Tire and Wheel Specifications

Radial Specifications

Size	Ply	Maximum Load (lb)	Pressure
ST145R12 LRD	8	1220	65PSI
ST145R12 LRE	10	1520	80PSI
ST175/80R13 LRC	6	1360	50PSI
ST185/80R13 LRD	8	1710	65PSI
ST205/75R14 LRC	6	1760	50PSI
ST205/75R14 LRD	8	2040	65PSI
ST215/75R14 LRD	8	2200	65PSI
ST205/75R15 LRC	6	1820	50PSI
ST205/75R15 LRD	8	2150	65PSI
ST225/75R15 LRC	6	2150	50PSI
ST225/75R15 LRD	8	2540	65PSI
ST225/75R15 LRE	10	2830	80PSI
ST235/75R15 LRC	6	2340	50PSI
ST235/75R15 LRD	8	2910	65PSI
ST235/80R16 LRE	10	3520	80PSI
ST235/85R16 LRE	10	3640	80PSI
ST235/85R16 LRF	12	3960	95PSI
ST235/80R16 LRG	14	4080	110PSI
ST235/85R16 LRG	14	4400	110PSI
LT225/75R16 LRE	10	2680 single/2470 dual	80PSI
LT235/85R16 LRE	10	3420 single/2778 dual	80PSI
LT235/85R16 LRG	14	3750	110PSI
LT315/70R17 LRD	8	3195 single/2910 dual	50PSI
215/75R17.5 LRH	16	4805 single/4546 dual	123PSI
235/75R17.5 LRH	16	6005 single/5675 dual	128PSI
245/70R19.5 LRG	14	4540 single/4410 dual	110PSI

Aluminum Wheel Specifications

Size	Bolt Pattern	Maximum Load (lb)
12x4	5-4.5	1520
13x5	5-4.5	1710
14x5	5-4.5	2200
15x5	5-4.5	2150
15x6	5-4.5	2200
15x6	6-5.5	2830
16x6	6-5.5	3300
16x6	8-6.5	4080
16x6	8-6.5 HD	4400
17.5x6.75	8-6.5 (9/16")	4850
17.5x6.75	8-6.5 (5/8")	6050

Steel Wheel Specifications

Size	Bolt Pattern	Maximum Load (lb)
8x7	5-4.5	1075
10x6	5-4.5	1535
12x4	5-4.5	1520
13x4.5	5-4.5	1710
14x5.5	5-4.5	2200
15x5	5-4.5	2150
15x5	5-5	2150
15x6	5-4.5	2200
15x6	5-5	2200
15x6	6-5.5	2830
16x6	6-5.5	3300
16x6	8-6.5	4080
16x6	8-6.5 HD	4400
17.5x6.75	8-6.5 (5/8")	6005