

## WARNING

### DEALER / CUSTOMER RESPONSIBILITY

With EZ Loader, your safety is our first concern. Please adhere to the following safety requirements so that your boating and trailering experience is both trouble-free and safe. Failure to comply may result in serious personal injury, death or extreme damage to your boat and trailer.

1. Torque wheel lug nuts to 85-95 ft. lbs. in stages as recommended on page 14 of the EZ Loader Owner's Operation Manual. Lug nuts must be re-torqued after the first 50 miles of use. Check lug nuts before every trip for proper torque.

*Loose lug nuts can cause wheel holes to elongate and stud to shear off.*

2. Keep tires inflated to the recommended pressure as stated on the tire. Check pressure before each trip.

***EZ LOADER IS NOT RESPONSIBLE FOR THESE AREAS LISTED ABOVE.***

*See other side*

3. Hitch ball and trailer coupler must be of the same size, and same rating. Coupler latch must fit secure over the ball, the coupler-locking device engaged, and safety chains must be attached before towing.
4. Since boat trailer wheels are put in water, it is important to check and lubricate bearings on a regular basis.

***EZ LOADER IS NOT RESPONSIBLE FOR THESE AREAS LISTED ABOVE.***

*See other side*

## WARNING

### DEALER / CUSTOMER RESPONSIBILITY

With EZ Loader, your safety is our first concern. Please adhere to the following safety requirements so that your boating and trailering experience is both trouble-free and safe. Failure to comply may result in serious personal injury, death or extreme damage to your boat and trailer.